

KATUALI

It has a great breaking strength and one of the best diameter/breaking strength ratios on today's market.

RIGGING ROPE



DESCRIPTION

A polyester rigging rope that is very flexible and has little elongation. In order to be used with all friction devices, it comes in 5 diameters: the "usual" 4, from 12 to 18 mm, but also in 10 mm. The additional diameter is ideal for the MICRO-CYLINDRE, but also for all everyday rigging tasks, whether to fell a tree or to rig a single branch... As a matter of fact, it is a very light rope, easy to use and with a great resistance.

Machinery Directive 2006/42/CE

Double braid - 16 strands
100 % polyester

TECHNICAL INFORMATION

Diameter	Weight	MBS	MBS with splice	Composition
10 mm (white and orange)	86 g/m	30 kN / WLL (coef. 7) : 4.3 kN	29 kN / WLL (coef. 7): 4.1 kN	53 % core, 47 % cover
12 mm (white and blue)	119 g/m	42 kN / WLL (coef. 7): 6 kN	40 kN / WLL (coef. 7): 5.7 kN	57 % core, 43 % cover
14 mm (white and green)	153 g/m	55 kN / WLL (coef. 7): 7.8 kN	52 kN / WLL (coef. 7): 7.4 kN	55 % core, 45 % cover

16 mm (white and red)	203 g/m	72 kN / WLL (coef. 7): 10 kN	10 kN / WLL (coef. 7): 10 kN	56 % core, 44 % cover
18 mm (white and black)	256 g/m	86 kN / WLL (coef. 7): 12.2 kN	78 kN / WLL (coef. 7): 11 kN	56 % core, 44 % cover

REFERENCES

FTC/K1050-V	length (m/ft) - 50 m (164 ft)splice - no splicediameter - 10 mm (0.39 in)
FTC/K1250-V	length (m/ft) - 50 m (164 ft)splice - no splicediameter - 12 mm (0.47 in)
FTC/K1450-V	length (m/ft) - 50 m (164 ft)splice - no splicediameter - 14 mm (0.55 in)
FTC/K1650-V	length (m/ft) - 50 m (164 ft)splice - no splicediameter - 16 mm (0.62 in)
FTC/K1850-V	length (m/ft) - 50 m (164 ft)splice - no splicediameter - 18 mm (0.7 in)
FTC/K1050	length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 10 mm (0.39 in)
FTC/K1250	length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 12 mm (0.47 in)
FTC/K1450	length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 14 mm (0.55 in)
FTC/K1650	length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 16 mm (0.62 in)
FTC/K1850	length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 18 mm (0.7 in)
FTC/K1065-V	length (m/ft) - 65 msplice - no splicediameter - 10 mm (0.39 in)
FTC/K1265-V	length (m/ft) - 65 msplice - no splicediameter - 12 mm (0.47 in)
FTC/K1465-V	length (m/ft) - 65 msplice - no splicediameter - 14 mm (0.55 in)
FTC/K1665-V	length (m/ft) - 65 msplice - no splicediameter - 16 mm (0.62 in)
FTC/K1865-V	length (m/ft) - 65 msplice - no splicediameter - 18 mm (0.7 in)
FTC/K1065	length (m/ft) - 65 msplice - 1 splicediameter - 10 mm (0.39 in)
FTC/K1265	length (m/ft) - 65 msplice - 1 splicediameter - 12 mm (0.47 in)
FTC/K1465	length (m/ft) - 65 msplice - 1 splicediameter - 14 mm (0.55 in)
FTC/K1665	length (m/ft) - 65 msplice - 1 splicediameter - 16 mm (0.62 in)
FTC/K1865	length (m/ft) - 65 msplice - 1 splicediameter - 18 mm (0.7 in)
FTC/K1070-V	length (m/ft) - 70 m (229.6 ft)splice - no splicediameter - 10 mm (0.39 in)
FTC/K1270-V	length (m/ft) - 70 m (229.6 ft)splice - no splicediameter - 12 mm (0.47 in)
FTC/K1470-V	length (m/ft) - 70 m (229.6 ft)splice - no splicediameter - 14 mm (0.55 in)
FTC/K1670-V	length (m/ft) - 70 m (229.6 ft)splice - no splicediameter - 16 mm (0.62 in)
FTC/K1870-V	length (m/ft) - 70 m (229.6 ft)splice - no splicediameter - 18 mm (0.7 in)

FTC/K1070	length (m/ft) - 70 m (229.6 ft)splice - 1 splicediameter - 10 mm (0.39 in)
FTC/K1270	length (m/ft) - 70 m (229.6 ft)splice - 1 splicediameter - 12 mm (0.47 in)
FTC/K1470	length (m/ft) - 70 m (229.6 ft)splice - 1 splicediameter - 14 mm (0.55 in)
FTC/K1670	length (m/ft) - 70 m (229.6 ft)splice - 1 splicediameter - 16 mm (0.62 in)
FTC/K1870	length (m/ft) - 70 m (229.6 ft)splice - 1 splicediameter - 18 mm (0.7 in)
FTC/KAT_10	length (m/ft) - By the metersplice - no splicediameter - 10 mm (0.39 in)
FTC/KAT_12	length (m/ft) - By the metersplice - no splicediameter - 12 mm (0.47 in)
FTC/KAT_14	length (m/ft) - By the metersplice - no splicediameter - 14 mm (0.55 in)
FTC/KAT_16	length (m/ft) - By the metersplice - no splicediameter - 16 mm (0.62 in)
FTC/KAT_18	length (m/ft) - By the metersplice - no splicediameter - 18 mm (0.7 in)

DOCUMENT

Instructions

Declaration of conformity

