

ANACONDA

Resistant, multi-purpose attachment sling.

ATTACHING SLING



DESCRIPTION

The ANACONDA sling can be used with pulleys, redirects, as ground anchoring, securing logs, Tyrolean traverses, etc. 4 diameters and their different lengths allow for the product to adapt to many situations.

4 diameters: 12 mm - 0.47 in (blue), 14 mm - 0.55 in (green), 16 mm - 0.62 in (red), 18 mm - 0.70 in (black).

Standard lengths :

12 mm: 2 m.

14 mm: 2.50 m and 3.50 m.

16 mm: 2.50 m and 3.50 m.

18 mm: 4.50 m.

Machinery Directive 2006/42/CE

100 % polyester double braid with polyurethane induction

50 % cover, 50 % core - 20 strands

TECHNICAL INFORMATION

Diameter	Weight	MBS
12 mm (0.47 in)	125 g/m (4.40 oz/ft)	45 kN / WLL: 6,4 kN

14 mm (0.55 in)	175 g/m (6.17 oz/ft)	55 kN / WLL: 7,8 kN
16 mm (0.62 in)	214 g/m (7.54 oz/ft)	67 kN / WLL: 9,5 kN
18 mm (0.70 in)	280 g/m (9.87 oz/ft)	76 kN / WLL: 11 kN

REFERENCES

FTC/EA-12-2	length (m/ft) - 2 m (6.5 ft) diameter - 12 mm (0.47 in)
FTC/EA-14-2.5	length (m/ft) - 2,50 m (8.2 ft) diameter - 14 mm (0.55 in)
FTC/EA-16-2.5	length (m/ft) - 2,50 m (8.2 ft) diameter - 16 mm (0.62 in)
FTC/EA-14-3.5	length (m/ft) - 3,50 m (11.4 ft) diameter - 14 mm (0.55 in)
FTC/EA-16-3.5	length (m/ft) - 3,50 m (11.4 ft) diameter - 16 mm (0.62 in)
FTC/EA-18-4.5	length (m/ft) - 4,50 m (14.7 ft) diameter - 18 mm (0.7 in)

DOCUMENT

Instructions

Declaration of conformity

